

Property of KOSCIUSKO Co Surveyor
Courthouse

Address 100 W CENTER ST.
WARSAW, IN 46580

Telephone 574-372-2367
Fax 574-372-2369
e mail www.kc.gov.com
or rkemper@kc.gov.com

This Book is manufactured of a High Grade 50% Rag Ledger Paper having a Water Resistant Surface, and is sewed with Nylon Waterproof Thread.

INDEX

TIPPECANOE	SECTION 19	PAGE 1
SCOTT	" 24	2
TURKEY CREEK	" 35	3
TIPPECANOE	" 3	4
VAN BUREN	" 25	5
TIPPECANOE	" 20	6
SCOTT NW CORNER & W 1/4 CORNER SEC 35		7
ETNA W 1/4 CORNER SEC 2-33-4		8
ETNA NW CORNER SEC 14-34-4		8
ETNA N 1/4 CORNER SEC 22-33-4		9
ETNA CENTER OF SEC 22-33-4		9
ETNA S 1/4 CORNER SEC 22-33-4		10
TURKEY CREEK S 1/4 CORNER SEC 34-34-7		11
TURKEY CREEK CENTER OF SECTION 34-34-7		11
TURKEY CREEK N 1/4 CORNER SECTION 34-34-7		12
TURKEY CREEK CENTER OF SECTION 27-34-7		12
TURKEY CREEK N 1/4 CORNER SECTION 27-34-7		13
TURKEY CREEK W 1/4 CORNER SECTION 10-34-7		13
WAYNE N 1/4 CORNER SEC 1-32-6		14
MONROE W 1/4 CORNER SECTION 5-31-7		15
MONROE CENTER OF SECTION 5-31-7		15
WAYNE SW CORNER SECTION 9-32-6		16
WAYNE S 1/4 CORNER SECTION 9-32-6		16

TIPPECANOE N $\frac{1}{4}$ CORNER SEC 16-33-7	17
MONROE CENTER OF SECTION 5-31-7	17
VAN BUREN E $\frac{1}{4}$ CORNER SEC 32-34-6	18
VAN BUREN NE CORNER SEC 32-34-6	18
TIPPECANOE SW CORNER SEC 1-33-7	19
ETNA NW CORNER SEC 13-33-4	20
ETNA W $\frac{1}{4}$ CORNER SEC 13-33-4	21
PRAIRIE NE CORNER SE $\frac{1}{4}$ SEC 17-33-5	22
PRAIRIE NW CORNER SE $\frac{1}{4}$ SEC 17-33-5	23
PRAIRIE SE CORNER SE $\frac{1}{4}$ SEC 17-33-5	23
SCOTT NE CORNER SEC 15-34-4	24
HARRISON N $\frac{1}{4}$ CORNER SEC 15-32-5	25
HARRISON NW CORNER SEC 15-32-5	26
HARRISON NW CORNER SEC 16-32-5	27
HARRISON N $\frac{1}{4}$ CORNER SEC 16-32-5	28
HARRISON NE CORNER SEC 15-32-5	29
HARRISON S $\frac{1}{4}$ CORNER SEC 13-32-5	30
SEWARD S $\frac{1}{4}$ CORNER SEC 10-31-5	31
VAN BUREN E $\frac{1}{4}$ CORNER SEC 27-34-6	32
VAN BUREN SE CORNER SEC 27-34-6	33
PRAIRIE CENTER OF SECTION 8-33-5	34
PRAIRIE E $\frac{1}{4}$ CORNER SECTION 8-33-5	35
PLAIN SW CORNER SECTION 28-33-6	36
WAYNE NW CORNER SECTION 8-32-6	37
WAYNE N $\frac{1}{4}$ CORNER SECTION 36-32-6	38

39	WAYNE	NE CORNER SECTION	36-32-6	39
	MONROE	NW CORNER SECTION	20-31-7	40
	PLAIN	S $\frac{1}{4}$ CORNER SECTION	25-33-6	41
	SCOTT	SE CORNER SECTION	25-34-4	42
	PLAIN	E $\frac{1}{4}$ CORNER SECTION	16-33-6	43
	PLAIN	SE CORNER SECTION	16-33-6	44
	MONROE	W $\frac{1}{4}$ CORNER SECTION	20-31-7	45
	SCOTT	E $\frac{1}{4}$ CORNER SECTION	25-34-4	46
	SCOTT	S $\frac{1}{4}$ CORNER SECTION	25-34-4	47
	SCOTT	SW CORNER SECTION	25-34-4	48
	SCOTT	S $\frac{1}{4}$ CORNER SECTION	26-34-4	49
	SCOTT	SE CORNER SECTION	34-34-4	50
	ETNA	SE CORNER SECTION	3-33-4	51
	ETNA	CENTER OF SECTION	15-33-4	52
	PRAIRIE	N $\frac{1}{4}$ CORNER SECTION	35-33-5	53
	WAYNE	SW CORNER SECTION	7-32-6	54
	HARRISON	CENTER OF SECTION	2-32-5	55
	PLAIN	N $\frac{1}{4}$ CORNER SECTION	10-33-6	56
	PLAIN	NE CORNER SECTION	11-33-6	57
	WAYNE	NW CORNER NE $\frac{1}{4}$ NE $\frac{1}{4}$	13-32-5	58
	WAYNE	SW CORNER SE $\frac{1}{4}$ SE $\frac{1}{4}$	13-32-5	59
	HARRISON	SW CORNER SECTION	32-32-5	60
	HARRISON	S $\frac{1}{4}$ CORNER SECTION	31-32-5	61
	SEWARD	NW CORNER SECTION	4-31-5	62
	FRANKLIN	NW CORNER SECTION	5-31-5	63
	HARRISON	S $\frac{1}{4}$ CORNER SECTION	36-32-4	64

	FRANKLIN	N $\frac{1}{4}$ CORNER SECTION	6-31-5	65
	FRANKLIN	NE CORNER SECTION	1-31-4	66
	HARRISON	S $\frac{1}{4}$ CORNER SECTION	35-32-4	67
	FRANKLIN	NW CORNER SECTION	1-31-4	68
	WASHINGTON	S $\frac{1}{4}$ CORNER SECTION	9-32-7	69
	WASHINGTON	COS SECTION	9-32-7	70
	WASHINGTON	COS SECTION	4-32-7	71
	WASHINGTON	N $\frac{1}{4}$ CORNER SECTION	4-32-7	72
	TIPPECANOE	SW CORNER SECTION	22-33-7	73
	PLAIN	E $\frac{1}{4}$ CORNER SECTION	1-33-6	74
	PLAIN	COS SECTION	1-33-6	75
	PLAIN	W $\frac{1}{4}$ CORNER SECTION	1-33-6	76
	VAN BUREN	SE CORNER SECTION	30-34-6	77
	VAN BUREN	S $\frac{1}{4}$ CORNER SECTION	30-34-6	78

DESCRIPTION

BEARING DISTANCE

TIPPECANOE

SECTION 19

R KEMPER

M KISSINGER


SW COR SE 1/4 NE 1/4

CRATSE

CR 450N

DESCRIPTION	BEARING	DISTANCE
SET PK NAIL - NIPSCO PP# ⁶⁷² / ₉₆₀ (W. FACE)	NW	12.95' ✓
SOUTH EDGE RR IRON POST	VNW	31.91'
SET PK NAIL N. FACE NIPSCO# ⁶⁷² / ₉₇₀	NE	55.49' 55.44'
FACE RR IRON POST	SE	32.15' ✓
1/24/18 JRM		
1/2" x 16" REBAR W/CAP 8.3' TO E/P	SE	37.30'
1/2" x 16" REBAR W/CAP 13' TO E/P	SW	39.70'

1/24/18 JRM		
FACE OF RR RAIL FCP AT BASE	NW	27.57'
NAIL IN B. CAP IN NIPSCO P POLE ⁶⁷⁰ / ₄₅₆	NW	29.43'
1/2" x 16" REBAR W/CAP 14.5' TO E/P 1050N	SE	39.65'
1/2" x 16" REBAR W/CAP 14.7' TO E/P 1050N	SW	41.70'



DESCRIPTION

BEARING DISTANCE

RAILROAD IRON POST

N

16.50'

1/2" IRON RE-BAR

NE

16.45'

1/2" IRON RE-BAR

SSW

21.30'

TURKEY CREEK

SECTION 35

1 1/4 POST

5/8" IRON RE-BAR

WOODS

X
X
X
X
X
WOVEN WIRE
FENCE

WOODS

FENCE REMAINS

X
X
RE-BAR121-COUNTY
GRASS RD-WAY
(CLEARED PATH)

• RE-BAR

WOODS

2 KEMPER

NORTH

7/01

35-34-7

DESCRIPTION

BEARING DISTANCE

CHISELED 4" IN LARGE STONE	NNE	20.65'
5/8" RE-BAR	NNW	31.35'
5/8" RE-BAR	SSW	23.30'
5/8" RE-BAR	SE	23.59'

TIPPECANOE


SECTION 3

EAST 1/4 POST

5/8" RE-BAR



7/5/01



DESCRIPTION	BEARING	DISTANCE
MAG NAIL IN PP#K5-02	W	18.35'
1/2" R-BAR W WITNESS CAP	NE	53.55'
1/2" R-BAR W WITNESS CAP	SE	38.97'

6/5/18 DEM

SET NAIL IN B. CAP POWER POLE	WNW	18.35'
SW COR 4'x10' CONC SIGN BASE	NE	51.43'
4" WELL	NE	76.5'
SET NAIL IN B. CAP POWER POLE	ESE	47.25'

FD HARRISON MONUMENT FLUSH


469 D

5

VAN BUREN

SECTION 25

RIKEMPER/MIKISSINGER



DESCRIPTION	BEARING	DISTANCE
1/2" IRON REBAR	NW	34.25'
1/2" IRON REBAR	NE	36.06'
1/2" IRON REBAR	SW	33.00'
1/2" IRON REBAR	SE	35.53'

8/6/18 SRM SET MAG NAIL W/ CO TAG OVER SPIKE

FO 3/4" IRON PIPE 8" DEEP N 20.30'

TIPPECANOE

32

SECTION 20

NE COR

RR SPIKE

ASPHALT

ARMSTRONG RD.

1/2" R-BAR


9-26-03

RR, MK


DESCRIPTION	BEARING	DISTANCE
✓ MAG NAIL IN PP	NE	34.18'
✓ MAG NAIL IN PP $\frac{473}{529}$	NW	66.50'
✓ MAG NAIL IN PP $\frac{582}{793}$	SW	33.35'
4/28/16 JRM		

✓ FACE RIP	WEST	19.83'
✓ FACE RIP	EAST	20.05'
✓ MAG NAIL E. FACE PP	NE	62.20'
4/28/16 JRM		

SCOTT



SCOTT



DESCRIPTION BEARING DISTANCE

✓ FACE RIP WEST 17.58'
 ✓ SW CORNER RIP NE 27.91'
 ✓ MAG NAIL S. FACE PP ENE 68.94'
 4/28/16 JRM

STATE ROAD 19 REPAVED 6/2016


MAG NAIL IN PP ^{REMC} 5657 NNW 37.43'
 FACE RIP WEST 24.68'
 MAG NAIL IN PP # 5653 ENE 96.76'
 SW COR HOUSE NE 118.53'

ETNA

4-2-04




W 1/4 Post 2-33-4




ETNA

4-2-04



NNW 14-33-4



HARRISON MONUMENT SET
 6/2016 INDOT

DESCRIPTION BEARING DISTANCE

MAG NAIL IN PP	SSE	97.99'
SW CORNER PHONE BOX	NE	36.18'
GONE STEEL FENCE POST	WEST	24.30'
4/28/16 SRM		
SET 1/2" REBAR W/CAP 6.3' TO E/P	SW	31.35'
SET 1/2" REBAR W/CAP 7.0' TO E/P	NW	28.05'
NAIL IN B. CAP IN POWER POLE STA 1061+75	SSE	97.68'

4/28/16 SRM		
SET 1/2" REBAR W/CAP	SE	41.92'
SET 1/2" REBAR W/CAP 5.48' FROM OTHER	SW	37.91'
1/2" RE-BAR	NW	42.19'
1/2" RE-BAR	SW	40.55'
SOUTH CORNER RIP	ESE	45.62'


NOTE: RESEARCH -
ALSO A PK THIS LOCATION -
SAME TIES AS ABOVE
MEASURE - REBAR NW 45.44'
REBAR SW 42.11'
RIP 42.00'

ETNA

4-2-04
R KEMPER
M KISSINGER




N 1/4 Post 22-33-4



STATE ROAD 19 REPAVED 6/2016

ETNA

4-2-04
R KEMPER
M KISSINGER



CENTER 22-33-4

IRON BAR IN CONG.
BEAN FIELD
LR 450N
RIP
RIP NOT USED
CORN FIELD

DESCRIPTION

BEARING DISTANCE

MAG NAIL E. FACE PR M940

NW

80.19'

GONE SE COR RIP

WEST

20.03'

NW COR RIP

EAST

20.03'

4/28/16 DR MOYER

SET 1/2" REBAR W/CAP

20.2' N OF RIP

NE

28.85'

ETNA

4-02-04


R KEMPER

M KISSINGER

5 1/4 Post 22-33-A

IRON ROD IN CONCRETE

(FLUSH)



HARRISON MONUMENT SET 6/2016 INDOT

DESCRIPTION

BEARING DISTANCE

1/2" RE-BAR W/KAP

NE

64.92'

1/2" RE-BAR W/KAP

SE

60.95'

MAG NAIL IN NIPSCO PP $\frac{623}{216}$

SW

44.20'

1/2" SPK N. SIDE PP # $\frac{659}{207}$

WNW

41.12'

MAG NAIL W. SIDE PP # $\frac{542}{207}$

ESE

64.22'

1/2" CAPPED RE-BAR

NE

56.38'

TURKEY CREEK

6-10-04

R KEMPER

M KISSINGER

5'14" POST 34-34-7

1/2" SPIKE (-.8')

NOTE: N 1/4
POST 3-33-7
IS 191' WEST

CR BROWN

BART'S SKI CENTER

TURKEY CREEK

6-10-04

R KEMPER

M KISSINGER

CENTER 34-34-7

PK NAIL

NOAA
NWIS
DOPPLER SITERD. TO SHARK L.
PUBLIC ACCESS

DESCRIPTION

BEARING, DISTANCE

✓ MAG NAIL E. FACE NIPSCO 802	1-056 W/SW	43.07'
1/2" R-BAR W/CAP	NE	48.15'
1/2" R-BAR W/CAP	SE	49.25'
10/25/17 SRM HARRISON MONUMENT BROKEN OFF SET MAG NAIL W/TAG OVER TOP		
SET 1/2" x 24" REBAR W/CAP 12.5' TO E/P SR13	SE	38.55'
SET 1/2" x 16" REBAR W/CAP 13.5' TO E/P SR13	NE	33.87'
NAIL W.B. CAP ON TOP OF WOOD FCP	W	44.86'

1/2" R-BAR W/CAP	SE	39.46'
1/2" R-BAR W/CAP	NE	44.69'
FACE TRIP	E	38.10'
MAG NAIL E FACE PP 659/175	W	38.24'

10/25/17 UPDATED SRM

HARRISON MONUMENT BROKEN OFF SET MAG NAIL N/CO TAG

TURKEY CREEK

N 1/4 POST 34-34-7

6-10-04

TR KEMPER

M KISSINGER

IRON PIN
(SQUARE)BILLBOARD
SIGN

R12900N

DITCH

TURKEY CREEK

CENTER 27-34-7

6-10-04

RD. IRON STAKE W/ RD CAP

TR KEMPER

M KISSINGER

R/W

R/W

659
175

RIP



DESCRIPTION	BEARING	DISTANCE
CONC. R/W MARKER	E-NE	85.05'
CONC. R/W MARKER	S-SE	82.80'
CONC. R/W MARKER	N-NW	84.38'
CONC. R/W MARKER	S-SW	82.80'

10/25/17 UPDATED SRM

HARRISON MONUMENT BROKEN OFF

NAIL IN B. CAP NIPSCO P. POLE	1064/809	NW	95.33'
1/2" x 16" REBAR w/CO CAP		NE	71.88'
MAG NAIL IN CO TAG CONC BASE LIGHT POLE		SE	67.43'
FO MAG NAIL NO TAG IN TURN LANE		SW	40.25'
SMALL MAG NAIL N 1.97'			
SMALL MAG NAIL E 2.05'			
SMALL MAG NAIL S 2.03'			

MAG NAIL IN PP JOY M1641	SW	51.13'
MAG NAIL IN PP $\frac{658}{744}$	NW	54.42'
1/2" R-BAR w/CAP	NE	44.10'



DESCRIPTION	BEARING	DISTANCE
RIP-NEAREST EDGE	SOUTH	18.00'
RIP-NEAREST EDGE	WNW	50.46'
1/2" RE-BAR W/BAR	NE	24.57'

ALSO SEE OLD SURVEY BK 4 P 31 1909

WAYNE

N 1/4 POST 1-32-6


9-13-05

R KEMPER

M KISSINGER


STONE WITH CHISELED "+" FOUND

18" DEEP (HARRISON TO)
BE SET



DESCRIPTION	BEARING	DISTANCE
CHISELED + IN CONC. WALK	NW	31.87' ✓
7/2/16 SRMOYER CONE " " " "	SW	37.25'
" " " "	SE	48.63' ✓
CHISELED "V" IN MH LID	NE	34.12'
7/2/16 SRMOYER 1/2 OF TOP NUT ON FIRE HYDRANT	NW	37.93'
MAG NAIL IN POWER POLE	NE	31.76'
MAG NAIL IN POWER POLE	SW	46.46'
FORR SPIKE 4" DEEP		

MAG NAIL IN DP	NW	37.97' ✓
CHISELED "V" IN W. SIDE MH	NNW	12.43' ✓
CHISELED + IN CONC. RET WALL	SSE	27.33'
" " " "	SSW	27.28'
7/26/16 SRM 1/2 OF RR RAIL FCP	N	17.58'



6/6/06

M. KISSINGER

J. ADAMS

MONUMENT: LENNING 1' SQUARE CONCRETE POST

TIES: NEAREST EDGE RIP 32.4' NORTH ✓

1/2" CAPPED REBAR 15.3' SOUTH ✓

" " " 39.4' N.WEST ✓

" " " 37.5' N.EAST GONE

7/17/18 MEK SRM - FO POST LEAVING SOUTH BADLY/


SET 1/2" REBAR W/CAP 20.2 EAST OF RIP NE 38.25'

6/8/06


M. KISSINGER

J. ADAMS

TIES: NICKEL 0.32' WEST



MONROE TWP.



VAN BUREN E 1/4 Post 32-34-6

- TIES
- NEAREST EDGE OF RIP: 29.9' WEST
 - 1/2" CAPPED REBAR (16'S OF DR NE E + 28'W OF ROAD E): 45.22'SW
 - " " " (28'N " FIELD ENT E + 28'E " " "): 35.15'NE
 - " " " (31'S " " " E + 38'E " " "): 53.96'SE
 - CENTER OF NICKEL 0.24'N


VAN BUREN NE COR. 32-34-6

- TIES
- "MAG" NAIL FOUND 0.92' E-SE
 - 1/2" CAPPED REBAR (62'N. OF CR 900N E + 33'E. OF ST. RD. #15 E): 70.5'N-NE
 - " " " (38'S " " " " + 32'E " " " " "): 47.94'SE
 - " " " (23'S " " " " + 36'W " " " " "): 43.62'SW
 - " " " (36'N " " " " + 42'W " " " " "): 56.58'NW
- | | | | |
|-------------------------------|------------|----|--------|
| FO MAG NAIL IN POWER POLE | | NW | 56.20' |
| FO MAG NAIL IN NIPSCO P. POLE | 680
557 | SE | 33.48' |
| - CENTER OF NICKEL 0.30'N | | | |
| FO MAG NAIL IN POWER POLE | | SW | 41.63' |
| E RAILROAD TRACKS | | E | 63.45' |

18

4/23/08 JK

PK FOUND
HARRISON SET




1/2" CAPPED REBAR SET

5/22/17

FO HARRISON MONUMENT

NOT FO

NOT FO



1/2" CAPPED REBAR SET

TIPPECANOE TWP. SW 1-33-7


- REF. TIES -

DESCRIPTION	BEARING	DISTANCE
- SMALL MAG NAIL W/WASHER	NW	7.00'
- " " " "	E	14.00'
- 1/2" CAPPED REBAR (2.5' N. OF UTILITY POLE, 17' W. OF PRIVATE STONE LANE, 20' S. OF ROAD 2)	S-SE	24.04'
- 1/2" CAPPED REBAR (21' N. OF ROAD 2)	N-NE	28.57'

11/3/08

19


MAG NAIL W/WASHER SET
WHERE PIPE/SPIKE WAS
REMOVED DURING CULVERT
INSTALLATION.



DESCRIPTION	BEARING	DISTANCE
SET MAG NAIL IN NE FACE OF FENCE POST	NW	35.61
SET MAG NAIL IN NW FACE OF P. POLE	NE	34.44
NW FACE OF A RR RAIL FCP	SE	27.20

ETNA TOWNSHIP SEC 13-33-4

20




DESCRIPTION

BEARING DISTANCE

DESCRIPTION	BEARING	DISTANCE
SE CORNER AT BASE OF A RR RAIL FCP	NW	28.71'
EAST FACE OF A RR RAIL FCP	W	19.75'
SET MAG NAIL IN TRANSFORMER POLE	NE	30.18'
FO RR SPIKE IN ROAD 4" DEEP	N	23.25'

ETNA TOWNSHIP SEC 13-33-4


21



DESCRIPTION	BEARING	DISTANCE
SET NAIL IN BOTTLE CAP IN NE FACE OF A POWER POLE	NW	28.20'
CENTER OF A RR RAIL FCP AT GROUND	SW	26.74'
SET 1/2" REBAR WITH WITNESS CAP	NE	33.95'

PRAIRIE

NE CORNER SE 1/4
SECTION 17-33-5




DESCRIPTION	BEARING	DISTANCE
S SOUTH FACE OF RR RAIL FCP	N	17.84'
C NORTH FACE OF RR RAIL FCP	S	17.85'
S POST TO POST		35.65'
SET 1/2" REBAR WITH WITNESS CAP	SW	26.64'


EAST FACE AT THE BASE OF A 15" SQ TAPERED CONCRETE FCP	W	20.21'
WEST FACE OF A RR RAIL FCP	E	20.22'
SET A NAIL IN A BOTTLE CAP IN THE NW FACE OF A POWER POLE	NE	33.18'
2/16/17		
NAIL IN TAG IN POWER POLE	SE	53.35'

PRAIRIE

NW CORNER SE 1/4
SECTION 17-33-5




SE CORNER SE 1/4
SECTION 17-33-5



DESCRIPTION	BEARING	DISTANCE
FO RR RAIL FCP LEAVING SOUTH	S	21.30'
SET 1/2" REBAR / CAP "SEC COR WITNESS"	SE	46.55'
SET 1/2" REBAR / CAP "SEC COR WITNESS"	NE	55.52'
NAIL IN B. CAP IN REMC POWER POLE 0291	NE	55.85'
10/11/16 - SET RR SPIKE AFTER PAVING	SRM	

HARRISON

25




FO PK NAIL 3" DEEP OVER A RR SPIKE IN CONC
PAVEMENT 8" DEEP
FO PK NAIL 0.22' WEST &
0.09' SOUTH ON SURFACE

DESCRIPTION	BEARING	DISTANCE
SET 1/2" REBAR WITH WITNESS CAP	NNW	23.71'
SET NAIL IN BOTTLE CAP IN ANCHOR POLE	NE	25.75'
SET 1/2" REBAR WITH WITNESS CAP	SW	35.76'
SET 1/2" REBAR WITH WITNESS CAP	SE	31.50'

10/11/16 - SET RR SPIKE AFTER PAVING - SRM

HARRISON


26



DESCRIPTION	BEARING	DISTANCE
NEAREST EDGE OF A RR RAIL FCP	SE	35.20'
SET NAIL IN BOTTLE CAP IN P. POLE	SSE	60.19'
SET 1/2" REBAR W/CAP	WSW	61.36'
SET 1/2" REBAR W/CAP	SSW	75.30'
MAG NAIL IN REMC POWER POLE	SE	34.94'
10/11/16 - SET MAG NAIL/WASHER OVER SPIKE	SRM	

HARRISON

27



DESCRIPTION


• BEARING DISTANCE

NEAREST EAST EDGE RR RAIL FCP	SSW	22.87'
SET 1/2" REBAR W/CAP	S	27.92'
SET 1/2" REBAR W/CAP	SE	57.41'
SET NAIL IN BOTTLE CAP IN E. FACE OF A POWER POLE	ESE	58.73'

10/11/16 - SET RR SPIKE AFTER PAVING - SRM

HARRISON

28



DESCRIPTION

BEARING DISTANCE

SET 1/2" REBAR W/WITNESS CAP

NE

25.25'

SET 1/2" REBAR W/WITNESS CAP

NW

31.87'

40.45' BETWEEN REBARS

SET NAIL IN BOTTLE CAP IN S. FACE
OF A REMC POWER POLE

SE

47.22'

10/26/17 DRM SET MAG NAIL W/CO TAG FROM WITNESSES

HARRISON

29

N
11/23/15
REMOVEDNE CORNER
SECTION 15-32-5GRASS
YARD

10.2'


BEAN FIELD

HORSE
PASTUREFD PK NAIL 3" DEEP
OVER A RR SPIKE
IN CONC PAVEMENT
7 1/2" DEEP

DESCRIPTION	BEARING	DISTANCE
FO 1/2" REBAR W/KISSINGER CAP	ENE	53.90'
FO MAG NAIL 1" DEEP	E	50.00'
¢ RR RAIL FCP	N	19.60'
¢ OF POST TO ¢ OF POST		39.35'


HARRISON

30



DESCRIPTION	BEARING	DISTANCE
1/2 RR RAIL FCP	S	20.00'
SET NAIL IN BOTTLE CAP IN E FACE OF POWER POLE	SE	18.92'

SEWARD



DESCRIPTION	BEARING	DISTANCE
FO PK NAIL IN SOUTH SIDE OF POWER POLE	NE	27.35'
WEST FACE OF RR RAIL FCP	SE	26.32'
SET 1/2" REBAR W/CAP 4.5' FROM E/P	NW	27.75'
SET 1/2" REBAR W/CAP 3.6' FROM E/P	SW	25.31'

VAN BUREN

N
2/11/16
JRM

YARD

CR 200 E

CR 950 N

FO MAG NAIL
FLUSHE 1/4 CORNER
SECTION 27-34-6

HANGING FILE Pt (122) FO STEEL BOLT 12/28/79

DESCRIPTION	BEARING	DISTANCE
FO PK NAIL IN WEST FACE OF POWER POLE	NE	50.39'
E OF A RR RAIL FCP	W	16.65'
SET 1/2" REBAR W/CAP 7.5' FROM E/P	WNW	23.32'
SET 1/2" REBAR W/CAP 14' FROM E/P	ENE	25.12'

VAN BUREN

SE CORNER
SECTION 27-34-6N
2/11/16
SRM

O

I


CR 200 E

FO RR SPIKE
2" DEEP

HANGING FILE Pt (113) RR SPIKE SET 12/28/79

DESCRIPTION	BEARING	DISTANCE
SET 1/2" REBAR W/CAP	NW	42.83'
SET 1/2" REBAR W/CAP	SW	28.00'
SET PK NAIL IN POWER POLE	SE	27.10'
£ RR RAIL FCP	S	20.00'

PRAIRIE



FO RR SPIKE 3" DEEP

REPLACED WITH 1/2" x 16" REBAR W/CAP

DUG A HOLE 3' DIA x 36" DEEP NO STONE

HANGING FILE PT 49 NO CORNER


SET HARRISON MONUMENT 7/26/16 SRM

DESCRIPTION

BEARING DISTANCE

SET 1/2" REBAR W/CAP	NE	25.65'
SET 1/2" REBAR W/CAP	SE	25.70'
FACE OF RR RAIL FCP	N	18.56'
€ OF RAIL TO € OF RAIL		37.8'

PRAIRIE



DESCRIPTION

BEARING DISTANCE

FO 4" DIA GALV. FENCE POST 6' TALL	NW	24.83'
FO PK NAIL IN NIPSCO P. POLE 636/856	SW	32.05'
NEAREST CORNER OF BRICK SIGN AT BASE	NE	6.90'
SET 1/2" REBAR W/CAP AT B/C END OF CURB	SE	25.90'


IRON ROD (1989) LONG & ASSOC. NOT FOUND

HANGING FILE Pt 38

NO STONE INDICATED IN RECORD BOOKS

WAYNE


37



DESCRIPTION	BEARING	DISTANCE
1/2" REBAR W/CAP 6' SOUTH OF FENCE POST	NW	47.20'
1/2" REBAR W/CAP IN FENCE ROW	NE	29.45'
FACE OF RR RAIL FCP	E	20.05'
NAIL IN BOTTLE CAP IN P. POLE	SE	61.62'

SURVEY RECORD BOOK 90 P. 3 (LONG) 5/9/86
 SURVEY RECORD BOOK 52 P. 69 (ECK) 3/31/79
 HANGING FILE PT 175

WAYNE




DESCRIPTION

BEARING DISTANCE

FACE OF A 6" X 10" BRIDGE BEAM FCP	W	19.83'
FACE OF A RR RAIL FCP	E	19.96'
SET 1/2" REBAR W/CAP	NE	40.43'
SET 1/2" REBAR W/CAP	SE	27.20'

WAYNE

39




SURVEY RECORD BOOK 62 Pg 34 (CMB) 6/18/82

DESCRIPTION

BEARING DISTANCE

NAIL IN BOTTLE CAP IN P. POLE	NW	46.32'
SW CORNER OF A 5" X 10" BRIDGE BEAM	ENE	48.02'
1/2" REBAR W/CAP	SE	39.64'
1/2" REBAR W/CAP	SW	48.06'

MONROE



PT 201 HANGING FILE - NO MONUMENT LISTED


NO STONE CALLED FOR

SURVEY RECORD BOOK 101 P. 11 LONG 11/24/87

DESCRIPTION	BEARING	DISTANCE
NAIL IN BOTTLE CAP IN P. POLE NIP 640 6020/526	NW	21.30'
1/2" REBAR W/ CAP IN FENCE ROW	NE	27.28
4 RR RAIL FCP	SSW	20.03'

PLAIN


41



DESCRIPTION	BEARING	DISTANCE
4 SW BOLT STATE STOP LIGHT POLE	NW	65.60'
SET 1/2" REBAR W/CAP	SE	39.40'
SET 1/2" REBAR W/CAP	SW	38.50'
OLD TIE NE COR PORCH AT STORE	SW	62.08'

HANGING FILE PT 85

SCOTT




DESCRIPTION

BEARING DISTANCE

SET NAIL IN BOTTLE CAP IN POWER POLE	W	19.16'
SET NAIL IN BOTTLE CAP IN POWER POLE	SE	24.83'
FD RR SPIKE IN RR TIE FENCE COR POST	E	17.42'

PLAIN

44



7/1/96 BROWER SURVEY


HANGING FILE PT 85 - CALLED FOR BRONZE MARKER

DESCRIPTION

BEARING DISTANCE

DESCRIPTION	BEARING	DISTANCE
CENTER OF A RR RAIL FCP	W	19.99'
SET NAIL IN BOTTLE CAP IN TRANSFORMER POLE	SW	26.21'
SET 1/2" REBAR W/CAP 7' FROM E/P	SE	21.77'

MONROE



DESCRIPTION

BEARING DISTANCE

FO 6" DIA 1. POST, SW FACE AT BASE

NE

26.30'

1/2 RR RAIL FCP .35' WIDE

W

20.48'

SET 1/2" REBAR W/CAP 12.5' TO E/P

SE

38.38'

SET MAG NAIL IN P POLE 626/025

NE

26.60'

SCOTT

N
4/20/16
JRM

STATE ROAD 19

E 1/4 CORNER

SECTION 25-34-4

SEE COR BOOK Pg 326

CR 950 N

12.5'


FO MAG NAIL
2" DEEP

PT 72 HANGING FILE

FO TWO WITNESS POINT IN OLD SURVEY FIELD BOOK


DESCRIPTION	BEARING	DISTANCE
FO OLD NAIL IN BOTTLE CAP IN POWER POLE 691/233	ESE	35.94'
FACE OF RR RAIL FCP	N	20.15'
S FACE 2-CHANNEL IRON FCP LEAVING E	S	20.20'
S SET 1/2" REBAR W/ CAP AT E EDGE OF A CONC HEADWAY FOR A 15" CMP 3.7' FROM E/P	SW	21.71'

SCOTT



DESCRIPTION	BEARING	DISTANCE
SET MAG NAIL IN P. POLE 677/735	NW	42.62'
SET MAG NAIL IN P. POLE 691/244	SW	32.00'
¢ OF A 2" DIA PIPE IN CONC FLUSH	NE	27.30'

SCOTT



DESCRIPTION

BEARING DISTANCE

NEAREST EDGE RR RAIL FCP

N

21.15'

NORTH FACE RR RAIL FCP

S

20.57'

MAG NAIL IN NORTH FACE P. POLE $\frac{1058}{372}$

SE

50.14'

SCOTT

49

4/26/16

S 1/4 CORNER

SECTION 26-34-4

STATE ROAD 19

H

FO BOAT SPIKE
8" DEEP

FO SMALL MAG NAIL 0.55' N
0.23' E FLUSH

HANGING FILE PT 82

STATE ROAD 19 REPAVED 6/2016

DESCRIPTION

BEARING DISTANCE


SET 1/2" REBAR W/CAP	13' FROM I. POST	NE	28.15'
FACE OF A 5 1/2" DIA I. POST FILLED W CONC		ENE	23.80'
SET 1/2" REBAR W/CAP	10.5' EAST OF E/P	SSW	30.92'
SECTION CORNER BOOK P ₃ 329 "I"			

NE CORNER SEC 3-33-4 ETNA TWP

SET MAG NAIL IN REMC P. POLE 2958	NE	32.73'
SET MAG NAIL IN NIPSCO P. POLE 294/519	NW	28.15'
SECTION CORNER BOOK P ₃ 33 "C"		

SCOTT


50



STATE ROAD 19 REPAVED 6/2016 BOTH CORNERS
ARE MAG NAILS FLUSH SET BY INDOT

DESCRIPTION	BEARING	DISTANCE
SW CORNER RR RAIL FCP	W	16.56'
FO PK NAIL IN WASHER IN P. POLE	NE	34.98'
FO PK NAIL IN WASHER IN P. POLE	ENE	63.28'

ETNA



DESCRIPTION

BEARING DISTANCE

E RR RAIL FCP

W

23.64'

SET 1/2" REBAR W/CAP 21.3' N OF RIP

NW

32.34'

ETNA

52

4/28/16
DRMCENTER OF SECTION
SECTION 15-33-4

N

O

H

O

STATE RD 19

FO SMALL
MAG NAIL FLUSH

STATE ROAD 19 REPAVED 6/2016

HANGING FILE PT 41

SECTION CORNER BOOK Pg 39 "E"

DESCRIPTION

BEARING DISTANCE

SET NAIL IN BOTTLE CAP IN TEL. POLE

NW


42.52'

E RE RAIL FCP

N

20.75'

PLAIN



DESCRIPTION

BEARING DISTANCE

SET NAIL IN BOTTLE CAP IN P. POLE

NE


36.34'

SET 1/2" REBAR W/CAP 7' FROM E/P

NW


39.45'

PLAIN



DESCRIPTION	BEARING	DISTANCE
MAG NAIL IN NIPSCO P. POLE 647/061	WNW	50.92'
MAG NAIL IN NIPSCO P. POLE 637/650	NNE	51.85'
MAG NAIL IN NIPSCO P. POLE 637/651	ENE	52.32'

WAYNE




DESCRIPTION

BEARING DISTANCE


MAG NAIL IN NIPSCO P. POLE 637/158	WNW	44.94'
MAG NAIL IN NIPSCO P. POLE 621/944	NNE	53.16
SET 1/2" REBAR W/ CAP 12.5' FROM E/P	SW	34.53'

WAYNE



DESCRIPTION	BEARING	DISTANCE
SET MAG NAIL IN POWER LIGHT POLE	NW	37.00'
SET 1/2" REBAR W/CAP BESIDE FCP	NNE	48.56'
BENCHMARK S145	NE	34.38'

HARRISON




DESCRIPTION	BEARING	DISTANCE
⊥ RR RAIL FCP AT THE TOP	N	22.77'
⊥ RR RAIL FCP	SE	46.12'
FO MAG NAIL FLUSH	W	136.6'

HARRISON




S/26/16
SEMOVER

S 1/4 CORNER
SECTION 31-32-5
HARRISON TWP Pt 187



DESCRIPTION	BEARING	DISTANCE
MAG NAIL IN P. POLE	NNE	27.25'
MAG NAIL IN P. POLE	SSE	79.35'
£ RR RAIL FCP AT BASE	SW	50.7'
FO PK NAIL IN £	E	136.6'

SEWARD



ALSO

NE CORNER
SECTION 5-31-5
FRANKLIN TWP PT 11

DESCRIPTION

BEARING DISTANCE

SET MAG NAIL IN P. POLE	SE	46.74'
SET MAG NAIL IN P. POLE	SSW	77.23'
SET 1/2" REBAR W/CAP 17.2 SOUTH E/P	SW	42.10'

5/18/17 SET 1/2" X 2 1/2" MAG NAIL W/ CO TAG PER TIES

FRANKLIN

63



5/27/16


DR MOYER

NW CORNER

SECTION 5-31-5

FRANKLIN TWP PT 9

STATE ROAD 25



22 900 25

FO BRONZE
MONUMENT
4" DEEPLOG - FIELD BOOK 1 Pg 326, INTERSECTED 4.00 CHNS
EAST (264') JULY 1, 1834

STONE - SURVEY RECORD BOOK 1 Pg 132 NOV 22, 1850

DESCRIPTION

BEARING DISTANCE

SET MAG NAIL IN P POLE

NE 20.30'

SET MAG NAIL IN P. POLE

SE 38.04'

SET MAG NAIL IN TEL. POLE

SW 34.50'

HARRISON

5/27/16
JR MOYER

5 1/4 CORNER

SECTION 36-32-4

HARRISON TWP PT 185

STATE ROAD 25

FO MAG NAIL FLUSH

DESCRIPTION

BEARING DISTANCE


SET 1/2" REBAR W/CAP 13.8' TO E/P	SW	32.37'
N FACE OF A 12" DIA CONC FCP AT BASE	SSE	24.42'
SET MAG NAIL IN P POLE	SE	42.48'

FRANKLIN

5/31/16
JRM
N

N 1/4 CORNER
FRAC SECTION 6-31-5
FRANKLIN TWP PT 8

STATE ROAD 25



STONE - SURVEY RECORD BOOK 1 Pg 153

DESCRIPTION	BEARING	DISTANCE
MAG NAIL IN P. POLE	NE	30.75'
SET 1/2" REBAR W/CAP 3' FROM E/P	SE	46.77'

FRANKLIN



5/31/16
SRM

NE CORNER

SECTION 1-31-4

FRANKLIN TWP Pt 7

STATE ROAD 25

CR 1000 W

RANGE 4 EAST

RANGE 5 EAST

FO MAG NAIL IN WASHER
FLUSH

FIELD NOTE BOOK Pg 419 & 443


KIMPEL SURVEY - MARCH 22, 1998 SET PK NAIL
#98-03-1942

DESCRIPTION

BEARING DISTANCE

DESCRIPTION	BEARING	DISTANCE
MAG NAIL IN REMC P POLE 1184 RO/HGT	WNW	45.45'
MAG NAIL IN REMC P POLE 1185 RO/HGT	NNW	59.90'
SET 1/2" REBAR W/CAP BETWEEN C. BASIN	NE	42.40'

HARRISON




DESCRIPTION

BEARING DISTANCE


SET 1/2" REBAR W/CAP 4' FROM WALK	NW	44.35
FO NAIL IN 3/4" IN NIPSCO P. POLE 637/852	NE	40.56'
SET 1/2" REBAR W/CAP 1' FROM WALK	SE	47.90'
NE BOLT OF RR SIGNAL BASE	SW	33.34'

FIELD NOTE BOOK 1 Pg 426 INTERSECTED CORRECTION LWE
JUNE 11, 1834

FRANKLIN



ST RD 25




FO BRONZE MONUMENT
5" DEEP

FO PL. NAIL 0.2' EAST
2" DEEP

DESCRIPTION	BEARING	DISTANCE
FO MAG NAIL IN WASHER, N FACE OF P. POLE	S	48.71'

WASHINGTON



DESCRIPTION

BEARING DISTANCE

FACE OF A RR RAIL FCP

W

18.05

FACE OF A 12" DIA CONC FCP

E


20.05'

SET 1/2" REBAR W/CAP 10' FROM E/P

NE


28.20'

WASHINGTON



DESCRIPTION	BEARING	DISTANCE
NEAREST CORNER RR RAIL FCP AT BASE	NW	46.78'
OUTSIDE CORNER OF CONC HEADWALL	NNW	40.6'
NAIL IN B. CAP IN TEL. POLE	NE	58.32'
NAIL IN B. CAP IN TEL. POLE	SE	39.06'
NAIL IN B. CAP IN TEL. POLE	SW	51.42'

WASHINGTON



DESCRIPTION

BEARING

DISTANCE

NAIL IN B. CAP IN P. POLE

NNE

48.64'

NAIL IN B. CAP IN P. POLE

ENE

60.76'

SET 1/2" REBAR W/CAP 6' FROM E/P

SE

47.18'

TIPPECANOE



6/1/16

JRM

CR 700 E

EMS B 48

SW CORNER

SECTION 22-33-7

TIPPECANOE TWP R₁ 111

CR 400 N

11.5'

FO MAG NAIL
IN WASHER
FLUSH


DESCRIPTION

BEARING DISTANCE

SET NAIL IN B. CAP IN P. POLE	NW	33.30'
SET NAIL IN B. CAP IN P. POLE	NNE	59.00'
SET NAIL IN B. CAP IN P. POLE	WSW	73.66'

SPIKE SET OVER I.P. FOUND 10/20/84 OK SURVEY F.B. 11 P. 77

PLAIN




DESCRIPTION

BEARING DISTANCE

DESCRIPTION	BEARING	DISTANCE
SET 1/2" REBAR W/CAP 9.5' FROM E/P	NW	28.73'
¢ RR RAIL FCD	N	20.65'
SET 1/2" REBAR W/CAP 10.5' FROM E/P	NE	29.80'

PLAIN

75



KIMPEL SURVEY 8/9/86 SURVEY BOOK 98 P. 38

DESCRIPTION


BEARING DISTANCE

SET 1/2" REBAR W/CAP 10.5' FROM E/P NW 39.44'

SET NAIL IN B. CAP IN P. POLE SE 87.53'

SET NAIL IN B. CAP IN P. POLE SW 44.10'

PLAIN




DESCRIPTION

BEARING DISTANCE

SET 1/2" REBAR W/CAP 8.7' FROM E/P	NW	45.57'
FO NAIL IN B. CAP IN 3" SQ FENCE POST	NNW	35.72'
FO NAIL IN B. CAP IN 10" DIA WOOD FENCE POST	NE	28.10'
SET 1/2" REBAR W/CAP 6.7' FROM E/P	ENE	35.21'

VAN BUREN



DESCRIPTION

BEARING DISTANCE

SET 1/2" REBAR W/CAP	6' FROM E/P	NE	44.34'
SET 1/2" REBAR W/CAP	8' FROM E/P	SE	44.73'
FO NAIL IN B. CAP IN 6" SQ WD F. POST		S	20.47'

VAN BUREN

78

